

Datasheet

1 / 2

E135-300F 0 dB (M6)

Flexible full $1/4\lambda$ spring loaded customer tunable antenna whip

Flexible customer tunable spring loaded antenna whip especially made for use with SX-Mount and Multimag on vehicle roof etc.

- CUSTOMER TUNABLE (BY CUTTING)
- [CUTTING TABLE](#) FOR TUNING SUPPLIED

ELECTRICAL SPECIFICATIONS

Frequency	135 - 300 MHz (2M-BAND)
Bandwidth	20 MHz
Impedance	50 ohm
Vswr	< 2.0
Polarisation	Vertical
Gain	0 dBd, 2.1 dBi
Max. Input Power	100 W



MECHANICAL SPECIFICATIONS

Color	Black
Height	Approx. 570 mm (Before cutting)
Weight	90 g
Mounting Place	On "E"-type mounts
Mounting Instruction	Antenna must be cut to specified frequency. Cutting Table included
Materials	Stainless steel, PE and brass
Operating Temperature	-40C to +70C
Connector	M6 Internal thread

ORDERING INFORMATION

P/N	E12254
P/N	E12254IP (Bulk packing)

PACKAGING INFORMATION

Type	Polybag or bulk
------	-----------------



The diagram shows a long, thin cable antenna. A dimension line above the cable indicates a length of 570. At the right end of the cable, there is a small, dark, cylindrical component. A dimension line above this component indicates a length of 15.75. The cable itself is black and has a textured, braided appearance.