

SATFIX-1 (PASSIVE)

Mobile bolt-on pasive GNSS antenna for roof mounting

Passive mobile GNSS antenna for through-hole roof mounting

- FOR NAVIGATION AND TRACKING PURPOSE
- LOW PROFILE DESIGN
- NON-CORROSIVE

ELECTRICAL SPECIFICATIONS

Frequency	1561.1 MHz, 1575.42 MHz, 1598.1 - 1605.4 MHz (GLONASS/GPS & Galileo/ BeiDou)
Impedance	50 ohm
Vswr	<2
Satellite System	GLONASS, GPS, Galileo and BeiDou
Polarisation	RHC (Right Hand Circular)

MECHANICAL SPECIFICATIONS

Color	Black
Height	15 mm
Weight	110 g
Diameter	Ø 48 mm
Mounting	Bolt-on with adhesive tape for effective sealing
Mounting Place	On horizontal surface
Mounting Instruction	Unobstructed view to satellites
Mounting hole	Ø13 - 20 mm
Build-in Depth	Approx. 17 mm
Materials	ABS, PE, brass and PCB
Operating Temperature	-40°C to +70°C
Connector	FME-male (Other types available)
Cable	0.15 m (Other lengths available)
Ingress Protection	IP65 (When mounted)



ORDERING INFORMATION

P/N	40236
P/N	40236IP (Bulk packing)

PACKAGING INFORMATION

Type	Bulk packing or individually packing in Polybag
------	---

