

Thuraya Passive Omnidirectional Antenna

Marine Antenna Kit

- Ready to use solutions for Thuraya X5-Touch, XT/XT-LITE, XT-PRO/XT-PRO DUAL and SatSleeve Hotspot
- Low profile design
- Easy mounting on any US-style Mounting Bracket with 1"-14NF threaded stud
- Sold in complete kits including Antenna, Extension cables and Adapters



ELECTRICAL SPECIFICATIONS

| | |
|------------------|-------------------|
| Frequency | 1525 - 1660.5 MHz |
| Impedance | 50 ohm |
| Satellite System | Thuraya |
| Polarisation | LHCP |
| Axial ratio | < 6 dB |
| Gain | 2 dBic |

MECHANICAL SPECIFICATIONS

| | |
|-----------------------|--|
| Color | White (non-glossy) |
| Height | 191.5 mm |
| Weight | 300 g |
| Diameter | Ø 95 mm |
| Mounting | On US-style Mounting Brackets with 1"-14NF threaded stud |
| Mounting Place | On marine vessel or landbased vehicle |
| Materials | ASA, PCB, copper and brass |
| Operating Temperature | -40°C to +70°C |
| Connector | N-female (Antenna) |
| Cable | (See "Ordering information") |
| Ingress protection | IP66 |
| Serial no. | On product label |

ORDERING INFORMATION

| | |
|-----------|---|
| 60601-043 | Antenna + 8 m LTR240 cable + Adapters |
| 60601-053 | Antenna + 8 m LTR240 cable + Adapters + Deck Mount |
| 60601-063 | Antenna + 8 m LTR240 cable + Adapters + Mast/Rail Mount |



PACKAGING INFORMATION

| | |
|--------|--------------------|
| Type | Hardbox |
| size | 250 x 250 x 265 mm |
| weight | Approx. 500 g |

